



HS/400LK

**Rivestimento in legno
tinta noce**

**Covering in solid wood
ancient-looking walnut**

Chiave a Doppia Mappa

- Struttura monoblocco in lamiera d'acciaio dello spessore di 2 mm.
- Spessore totale del battente 50 mm.
- Serratura di sicurezza a 6 leve con chiave a doppia mappa (2 chiavi in dotazione).
- Estrazione della chiave impossibile a catenacci rientrati.
- 5 catenacci in acciaio nichelato Ø 22 mm.
- Rastrelliera e base in legno massello verniciato.
- Tesoretto interno portamunizioni con serratura a cilindro.
- Fori di ancoraggio sulla base e sullo schienale (4+4).

HS/400LK: • con tesoretto - 7 fucili

HS/600LK: • con tesoretto - 11 fucili

Double-Bitted Key

- One-piece steel construction with a body's thickness of 2 mm.
- Total thickness (with lock panel) : 50 mm.
- Security lock with 6 levers and double-bitted key (2 keys supplied).
- Key-retaining lock in open position.
- 5 nickel-plated steel bolts Ø 22 mm.
- Painted solid wood supports and base for rifles.
- Internal security box with cylinder lock.
- Pre-drilled anchor holes on floor and wall mounting (4+4).

HS/400LK • with sec. box - 7 rifles

HS/600LK: • with sec. box - 11 rifles



| Art Code | Misure esterne mm. External dim. mm. | | | Misure interne mm. Internal dim. mm. | | | Dim. porta mm. Door dim. mm. | | Numero catenacci Number of bolts | | Peso Weight | Litri Volume |
|-----------------|---|--------|--------|---|--------|--------|---------------------------------|--------|-------------------------------------|------|----------------|-----------------|
| | Alt/H | Larg/W | Prof/D | Alt/H | Larg/W | Prof/D | Alt/H | Larg/W | Oriz/Horiz | Vert | Kg | Lt |
| HS/400LK | 1605 | 450 | 370 | 1300* | 360 | 265 | 1410 | 280 | 3 | 1+1 | 70 | 134 |
| HS/600LK | 1605 | 625 | 370 | 1300* | 530 | 265 | 1410 | 430 | 3 | 1+1 | 89 | 197 |

* Esclusa l'altezza della cassetta interna

* Excluding the high of security box