



CM/5

- Frontale 10 mm
- Porta 10 mm
con protezione manganese
- Taglio Laser

- *Front 10 mm*
- *Door 10 mm*
with manganese protection
- *Laser Cut*



CERTIFICATA A
NORMA EUROPEA
UNI EN 14450-S2
CERTIFIED TO
EUROPEAN STANDARD
EN 14450-S2



Mechanical Combination with Disc

- 10 mm thick door, consisting in 3 laser-cut steel plates, of which the middle one is made of special manganese steel in order to offer more resistance to drilling attempts.
- Security combination lock EN 1300 certified, with 3 internal coaxial discs (1.440.000 combinations allowed).
- Recessed control handle and combination dial.
- Nickel-plated rotating steel bolts Ø 22 mm.
- Lock mechanism protected by a manganese-steel plate.
- Special door battens for exceptional resistance against robbery attempts using a sledge hammer.
- Strong internal welding realised by a robot-controlled system.
- Front panel seam-welded to the casing by a robot-controlled system.
- Removable internal shelf.
- Anchor tongues on the 4 back side against jerks-attempts.
- Oven dried thermo-hardening powder painting.

Art Code	Misure esterne mm.			Misure interne mm.			Dim. porta mm.		Numero catenacci		Peso Kg	Litri Lt
	Alt/H	Larg/W	Prof/D	Alt/H	Larg/W	Prof/D	Alt/H	Larg/W	Oriz/Horiz	Vert		
CM/4	270	390	200	245	365	150	195	300	2	-	18	14
CM/4L	270	390	240	245	365	190	195	300	2	-	19	18
CM/5	340	460	200	315	435	150	265	370	3	1+1	25	21
CM/5L	340	460	240	315	435	190	265	370	3	1+1	26	27
CM/6	420	480	230	395	455	180	345	390	3	2+2	33,5	33
CM/6L	420	480	280	395	455	230	345	390	3	2+2	34,5	43