



070 SDBK



Chiave a Doppia Mappa

- Alta protezione contro il fuoco: resistenza da 60 a 90 min. secondo il modello in condizioni di esposizione al fuoco ad una temperatura di 1010°C.
- Serratura ad alta sicurezza testata EN 1300 con chiave femmina a doppia mappa.
- Cassa interna supplementare costituita da pannelli di materiale melaminico e da specifiche protezioni che hanno funzione di isolante termico.
- Le guarnizioni della cassa interna e le scanalature della porta esterna assicurano la tenuta ermetica a liquidi, aria, vapore e fumo.
- Protezione contro i campi magnetici ed i fenomeni elettrostatici.
- Piedini in gomma alla base.



Double-Bitted Key

- High fire protection: from 60 min. up to 90 min. fire resistance, depending on the model, at a constant temperature of 1010°C.*
- Lock controlled by a high security lock with double-bitted key, EN 1300 certified.*
- Additional internal box, made of melamine panels and heat insulating materials.*
- The gaskets on the internal box and the grooves on the external door ensure a hermetic seal against liquids, air, gas, steam and smoke.*
- Protection against magnetic fields and electrostatic phenomena.*
- Equipment with rubber support feet on the bottom.*

Art	Misure esterne mm.			Misure interne mm.			Resistenza al fuoco	Ripiani	Peso	Litri
Code	External dim. mm.			Internal dim. mm.			Fire Resistance	Shelves	Weight	Volume
125 SDBK	Alt/H	Larg/W	Prof/D	Alt/H	Larg/W	Prof/D	Minuti/Min	N°	Kg	Lt
125 SDBK	420	352	433	224	157	206	60 - data/dis	1	43	7
530 SDBK	522	404	440	314	197	201	60 - data/dis	1	65	12
070 SDBK	695	500	500	419	277	231	90 - data/dis	1	117	27

Art	Capacità interna						
	Internal Capacity						
125 SDBK	4mm DAT	8mm AIT	CD	DLT	LTO/Utrium	LTO/Utrium (without case)	3590 Cartridge (without case)
125 SDBK	74	33	30	16	-	22	12
530 SDBK	150	54	53	20	-	36	22
070 SDBK	312	168	111	62	-	96	64